

Application											
04000 0044 Parakuru Curtara Managaran											
01969 - 2014 Roadway System Management											
02110 - TH 55 CMAQ											
Regional Solicitation - Roadways Including Multimodal Elements											
Status: Submitted											
Submitted Date:	11/26/2014 11:	27 AM									
Primary Contact											
Filliary Contact											
Name:*		Michael	Joseph	Fairbanks							
	Salutation	First Name	Middle Name	Last Name							
Title:	Principal Engin										
Department:	MnDOT Metro	Traffic									
Email:	mike.fairbanks	@state.mn.us									
Address:	1500 West Cou	ınty B-2									
*	Roseville	Minnesot	a	55113							
	City	State/Province	Э	Postal Code/Zip							
Phone:*	651-234-7819										
	Phone		Ext.								
Fax:	651-234-7850										
What Grant Programs are you most interested in?	Regional Solicitation - Roadways Including Multimodal Elements										

Organization Information

Name: STATE OF MN

Jurisdictional Agency (if different):

Organization Type: State Government

Organization Website:

Address: MN DOT

MS725

1500 W COUNTY RD B2 #250

ROSEVILLE Minnesota 55113

City State/Province Postal Code/Zip

County: Ramsey

Phone:* 651-366-3452

Ext.

Fax:

PeopleSoft Vendor Number 0000024577A36

Project Information

Project Name TH 55 CMAQ

Primary County where the Project is Located Dakota

Jurisdictional Agency (If Different than the Applicant):

The Signal Re-timing and Coordination Project will execute a very timely signal coordination project for TH 55 in the city of Hastings. The proposed scope of this project is as follows:

Brief Project Description (Limit 2,800 characters; approximately 400 words)

Advanced signal coordination and re-timing of 5 signal as well as cabinet upgrades; and deployment of 5 Closed Circuit Television (CCTV) cameras to support real-time signal timing plan changes to be executed by the Minnesota Department of Transportation (MnDOT) Arterial Signals Group.

TH 55 is a Non-Freeway Principal Arterial.

Include location, road name/functional class, type of improvement, etc.

Project Length (Miles)

1.9

Connection to Local Planning:

Reference the name of the appropriate comprehensive plan, regional/statewide plan, capital improvement program, corridor study document [studies on trunk highway must be approved by MnDOT and the Metropolitan Council], or other official plan or program of the applicant agency [includes Safe Routes to School Plans] that the project is included in and/or a transportation problem/need that the project addresses. List the applicable documents and pages.

2030 Transportation Policy Plan (amended 2013)

Connection to Local Planning

Statewide Multimodal Transportation Plan

Project Funding

Are you applying for funds from another source(s) to implement this project?

No

If yes, please identify the source(s)

Federal Amount \$288,000.00

Match Amount \$72,000.00

Minimum of 20% of project total

Project Total \$360,000.00

Match Percentage 20.0%

Minimum of 20%

Compute the match percentage by dividing the match amount by the project total

Source of Match Funds Safety Capacity (State Funds)

Preferred Program Year

Select one: 2019

MnDOT State Aid Project Information: Roadway Projects

County, City, or Lead Agency MnDOT

Functional Class of Road Non-Freeway Principal Arterial

Road System Trunk Highway

TH, CSAH, MSAS, CO. RD., TWP. RD., CITY STREET

Name of Road TH 55

Example; 1st ST., MAIN AVE

Zip Code where Majority of Work is Being Performed 55033

(Approximate) Begin Construction Date 07/02/2018
(Approximate) End Construction Date 06/28/2019

LOCATION

From:

(Intersection or Address)

Do not include legal description; Include name of roadway if majority of facility runs adjacent to a single corridor.

To:

(Intersection or Address)

General Sebian Drive

Type of Work Signal

Examples: grading, aggregate base, bituminous base, bituminous surface, sidewalk, signals, lighting, guardrail, bicycle path, ped ramps, bridge, Park & Ride, etc.)

Old Bridge/Culvert? No

New Bridge/Culvert?

Structure is Over/Under (Bridge or culvert name):

Specific Roadway Elements

CONSTRUCTION PROJECT ELEMENTS/COST ESTIMATES	Cost
Mobilization (approx. 5% of total cost)	\$18,000.00
Removals (approx. 5% of total cost)	\$0.00
Roadway (grading, borrow, etc.)	\$0.00
Roadway (aggregates and paving)	\$0.00
Subgrade Correction (muck)	\$0.00
Storm Sewer	\$0.00
Ponds	\$0.00
Concrete Items (curb & gutter, sidewalks, median barriers)	\$0.00
Traffic Control	\$18,000.00
Striping	\$0.00
Signing	\$0.00
Lighting	\$0.00
Turf - Erosion & Landscaping	\$0.00
Bridge	\$0.00
Retaining Walls	\$0.00
Noise Wall	\$0.00
Traffic Signals	\$324,000.00
Wetland Mitigation	\$0.00
Other Natural and Cultural Resource Protection	\$0.00
RR Crossing	\$0.00
Roadway Contingencies	\$0.00

Other Roadway Elements \$0.00

Totals \$360,000.00

Specific Bicycle and Pedestrian Elements	
CONSTRUCTION PROJECT ELEMENTS/COST ESTIMATES	Cost
Path/Trail Construction	\$0.00
Sidewalk Construction	\$0.00
On-Street Bicycle Facility Construction	\$0.00
Right-of-Way	\$0.00
Pedestrian Curb Ramps (ADA)	\$0.00
Crossing Aids (e.g., Audible Pedestrian Signals, HAWK)	\$0.00
Pedestrian-scale Lighting	\$0.00
Streetscaping	\$0.00
Wayfinding	\$0.00
Bicycle and Pedestrian Contingencies	\$0.00
Other Bicycle and Pedestrian Elements	\$0.00
Totals	\$0.00
Specific Transit and TDM Elements	
CONSTRUCTION PROJECT ELEMENTS/COST ESTIMATES	Cost
Fixed Guideway Elements	\$0.00
Stations, Stops, and Terminals	\$0.00
Support Facilities	\$0.00
Transit Systems (e.g. communications, signals, controls fare collection, etc.)	\$0.00
Vehicles	\$0.00
Transit and TDM Contingencies	\$0.00
Other Transit and TDM Elements	\$0.00
Totals	\$0.00
Transit Operating Costs	

Cost

\$0.00

OPERATING COSTS

Transit Operating Costs

Totals \$0.00

Totals

Total Cost \$360,000.00

Construction Cost Total \$360,000.00

Transit Operating Cost Total \$0.00

Requirements - All Projects

All Projects

1. The project must be consistent with the goals and policies in these adopted regional plans: Thrive MSP 2040 (2014), the 2030 Transportation Policy Plan (amended 2013), and the 2030 Water Resources Management Policy Plan (2005).

Check the box to indicate that the project meets this requirement. Yes

2.Applicants that are not cities or counties in the seven-county metro area with populations over 5,000 must contact the MnDOT Metro State Aid Office prior to submitting their application to determine if a public agency sponsor is required.

Check the box to indicate that the project meets this requirement. Yes

3. Applicants must not submit an application for the same project in more than one funding sub-category.

Check the box to indicate that the project meets this requirement. Yes

4.The requested funding amount must be more than or equal to the minimum award and less than or equal to the maximum award. The cost of preparing a project for funding authorization can be substantial. For that reason, minimum federal amounts apply. Other federal funds may be combined with the requested funds for projects exceeding the maximum award, but the source(s) must be identified in the application. Expansion, reconstruction/modernization, and bridges must be between \$1,000,000 and \$7,000,000. Roadway system management must be between \$250,000 and \$7,000,000.

Check the box to indicate that the project meets this requirement. Yes

5. The project must comply with the Americans with Disabilities Act.

Check the box to indicate that the project meets this requirement. Yes

6. The project must be accessible and open to the general public.

Check the box to indicate that the project meets this requirement. Yes

7.The owner/operator of the facility must operate and maintain the project for the useful life of the improvement.

Check the box to indicate that the project meets this requirement. Yes

8. The project must represent a permanent improvement with independent utility. The term independent utility means the project provides benefits described in the application by itself and does not depend on any construction elements of the project being funded from other sources outside the regional solicitation, excluding the required non-federal match. Projects that include traffic management or transit operating funds as part of a construction project are exempt from this policy.

Check the box to indicate that the project meets this requirement. Yes

9. The project must not be a temporary construction project. A temporary construction project is defined as work that must be replaced within five years and is ineligible for funding. The project must also not be staged construction where the project will be replaced as part of future stages. Staged construction is eligible for funding as long as future stages build on, rather than replace, previous work.

Check the box to indicate that the project meets this requirement. Yes

10. The project applicant must send written notification regarding the proposed projected to all affected communities and other levels and units of government prior to submitting the application.

Check the box to indicate that the project meets this requirement. Yes

Requirements - Roadways Including Multimodal Elements

Expansion and Reconstruction/Modernization Projects Only

1. The project must be designed to meet 10-ton load limit standards.

Check the box to indicate that the project meets this requirement.

2.Federal funds are available for roadway construction and reconstruction on new alignments or within existing right-of-way, including associated construction and excavation, bridges, or installation of traffic signals, signs, utilities, bikeway or walkway components and transit components.

The project must exclude costs for right-of-way, studies, preliminary engineering, design, or construction engineering. Noise barriers, drainage projects, fences, landscaping, etc., are not eligible for funding unless included as part of a larger project, which is otherwise eligible.

Check the box to indicate that the project meets this requirement.

Bridge Projects Only

3. The bridge project must be identified as a Principal Arterial (Non-Freeway facilities only) or A Minor Arterial as shown on the latest TAB approved roadway functional classification map.

Check the box to indicate that the project meets this requirement.

4.Bridges selected in previous Bridge Improvement and Replacement solicitations (1994 2011) are not eligible. A previously selected project is not eligible unless it has been withdrawn or sunset prior to the deadline for proposals in this solicitation.

Check the box to indicate that the project meets this requirement.

5.Projects requiring a grade-separated crossing of a Principal Arterial of freeway design must be limited to the federal share of those project costs identified as local (non-MnDOT) cost responsibility using MnDOTs Cost Participation for Cooperative Construction Projects and Maintenance Responsibilities manual. In the case of a federally funded trunk highway project, the policy guidelines should be read as if the funded trunk highway route is under local jurisdiction.

Check the box to indicate that the project meets this requirement.

6. The bridge must carry vehicular traffic. Bridges can carry traffic from multiple modes. However, bridges that are exclusively for bicycle or pedestrian traffic must apply under one of the Bicycle and Pedestrian Facilities sub-categories. Rail-only bridges are ineligible for funding.

Check the box to indicate that the project meets this requirement.

7. The length of the bridge must equal or exceed 20 feet.

Check the box to indicate that the project meets this requirement.

8. Project limits for bridge projects are limited from abutment to abutment.

Check the box to indicate that the project meets this requirement.

9. The project must exclude costs for studies, preliminary engineering, design, construction engineering, and right-of-way.

Check the box to indicate that the project meets this requirement.

Bridge Replacement Projects Only

10.The bridge must have a sufficienty rating less than 50. Additionally, it must also be classified as structurally deficient or functionally obsolete.

Check the box to indicate that the project meets this requirement.

Bridge Rehabilitiation Projects Only

Check the box to indicate that the project meets this requirement.

Other Attachments

File Name	Description	File Size
2110 State of MN HSIP.pdf	Crash B/C	31 KB
RdwayAreaDef.pdf	Roadway Area Definition	1.2 MB
RegionalEcon.pdf	Regional Economy	790 KB
SocioEcon.pdf	Socio Economic	788 KB
TransitCon.pdf	Transit Connections	809 KB

Measure A: Functional Classification

Address how the project fulfills its role in the regional economy as identified by its current functional classification. If the project serves a system of routes, respond using the route with the highest functional classification. This system must include a Non-Freeway Principal Arterial or an "A" Minor Arterial.

Reference the Roadway Area Definition map generated at the beginning of the application process. Report the total area and project length, as depicted on the Roadway Project Summary map, to calculate the average distance between the project route (highest functional classification) and the closest parallel A Minor Arterials or Principal Arterials on both sides of the project.

Upload the "Roadway Area Definition" map used for this measure.

 Area
 4.598

 Project Length
 1.92

 Average Distance
 2.3948

Upload Map TH 55 CMAQ Roadway Area.pdf

Measure B: Current Heavy Commercial Traffic

Location TH 55 @ Jacob Ave.

Current daily heavy commercial traffic volume 1600.0

Measure C: Project Location Relative to Jobs, Manufacturing and Education

Select all that apply:

Direct connection to or within a mile of a Job Concentration

Direct connection to or within a mile of a Manufacturing/Distribution Location

Direct connection to or within a mile of an Educational Institution Yes

Project provides a direct connection to or within a mile of an existing local activity center identified in an adopted county or city plan

County or City Plan Reference

Response (Limit 700 characters; approximately 100 words)

Upload Map TH 55 CMAQ Regional Economy.pdf

Measure A: Current Daily Person Throughput

Location TH 55 @ Pleasant Drive

Current AADT Volume 17500.0

Existing Transit Routes on the Project N/A

Response - Daily Person Throughput

Average Annual Daily Transit Ridership 2138.0

Current Daily Person Throughput 24888.0

Measure B: 2030 Forecast ADT

Use Metropolitan Council model to determine forecast (2030) ADT

volume

METC Staff - Forecast (2030) ADT volume 26700.0

OR

Approved county or city travel demand model to determine

forecast (2030) ADT volume

Forecast (2030) ADT volume 0

Measure A: Project Location and Impact to Disadvantaged Populations

Select one:

Project located in Racially Concentrated Area of Poverty

Project located in Concentrated Area of Poverty

Projects census tracts are above the regional average for

population in poverty or population of color

Yes

Project located in a census tract that is below the regional average for population in poverty or populations of color or includes children, people with disabilities, or the elderly.

Response (Limit 1,400 characters; approximately 200 words)

Upload Map TH 55 CMAQ Socio-Economic.pdf

Measure B: Affordable Housing

City/Township Segment Length (Miles)

Hastings 1.9

2

Total Project Length

Total Project Length 1.9

Affordable Housing Scoring - To Be Completed By Metropolitan Council Staff

City/Township	Segment Length (Miles)	Total Length (Miles)	Score	Segment Length/Total Length	Multiplied by Segment percent	
Hastings	1.9	1.9	70.0	1.0	70.0	
		2	70	1	70	

Affordable Housing Scoring - To Be Completed By Metropolitan Council Staff

Total Project Length (Miles) 1.9

Total Housing Score 70.0

Measure A: Equipment Improvements and Installation Year

Equipment to be Improved Signal Cabinets, Comm Equipment, and Controllers

Date of Equipment Installation 04/15/1993

Measure A: Cost Effectiveness of Vehicle Delay Reduction

Total Project Cost from Cost Sheet \$360,000.00

Total Peak Hour Vehicle Delay Without The Project 210.0

Total Peak Hour Vehicle Delay With The Project 170.0

Total Peak Hour Vehicle Delay Reduced by Project 40.0

Cost Effectiveness \$9,000.00

Synchro or HCM Reports TH 55.pdf

Measure B: Cost Effectiveness of Emissions Reduction

Total Project Cost from Cost Sheet \$360,000.00

Total Peak Hour Kilograms Reduced by Project 0.5

Cost Effectiveness \$720,000.00

Synchro or HCM Reports TH 55 - Before.syn

Measure A: Benefit/Cost of Crash Reduction

Project Benefit/Cost Ratio 2.09

Worksheet Attachment TH55, TH61 to General Sebian Dr.xls

Measure A: Transit Connections

Existing Routes Directly Connected to the Project N/A

Planned Transitways directly connected to the project (alignment

and mode determined and identified in the 2030 TPP)

Upload Map TH 55 CMAQ Transit Connections.pdf

N/A

Response

Met Council Staff Data Entry Only

Route Ridership 0

Transitway Ridership 0

Measure B: Bicycle and Pedestrian Connections

There is a Mountain Bike Trail (name unknown)

which has access to the TH 55 corridor near General Sieben Drive. Pedestrian accommodations

are provided at the following intersections (most of

which are ADA compliant): TH 61, Pine Street,

River Street, Westview Drive, Pleasant Drive, and General Sieben Drive with TH 55. Throughout the

corridor there are numerous commercial and mixed

use attractions.

Measure C: Multimodal Facilities

Response (Limit 1,400 characters; approximately 200 words)

Response (Limit 1,400 characters; approximately 200 words)

There are no bicycle, pedestrian, or transit elements included as part of this project. There is a Mountain Bike Trail (name unknown) which has access to the TH 55 corridor near General Sieben Drive. Pedestrian accommodations are provided at the following intersections (most of which are ADA compliant): TH 61, Pine Street, River Street, Westview Drive, Pleasant Drive, and General Sieben Drive with TH 55. There are no Park and Ride or transit facilities on this corridor.

Transit Projects Not Requiring Construction

If the applicant is completing a transit or TDM application, only Park-and-Ride and other construction projects require completion of the Risk Assessment below. Check the box below if the project does not require the Risk Assessment fields, and do not complete the remainder of the form. These projects will receive full points for the Risk Assessment.

Check Here if Your Transit Project Does Not Require Construction

Measure A: Risk Assessment	
1)Project Scope (5 Percent of Points)	
Meetings or contacts with stakeholders have occurred	Yes
100%	
Stakeholders have been identified	
40%	
Stakeholders have not been identified or contacted	
0%	
2)Layout or Preliminary Plan (5 Percent of Points)	
Layout or Preliminary Plan completed	Yes
100%	
100% Layout or Preliminary Plan started	
Layout or Preliminary Plan started	
Layout or Preliminary Plan started 50%	

3)Environmental Documentation (10 Percent of Points)

EIS EΑ

PM	
Document Status:	
Document approved (include copy of signed cover sheet)	100%
Document submitted to State Aid for review	75%
Document in progress; environmental impacts identified	
50%	
Document not started	Yes
0%	
Anticipated date or date of completion/approval	
4)Review of Section 106 Historic Resources (15 Percent of	Points)
No known potential for archaeological resources, no historic resources known to be eligible for/listed on the National Register of Historic Places located in the project area, and project is not located on an identified historic bridge	Yes
100%	
Historic/archeological review under way; determination of no historic properties affected or no adverse effect anticipated	
80%	
Historic/archaeological review under way; determination of adverse effect anticipated	
40%	
Unknown impacts to historic/archaeological resources	
0%	
Anticipated date or date of completion of historic/archeological review:	
Project is located on an identified historic bridge	
5)Review of Section 4f/6f Resources (15 Percent of Points)	
(4f is publicly owned parks, recreation areas, historic sites, wildlife or w. Conservation Funds were used for planning, acquisition, or development	
No Section 4f/6f resources located in the project area	Yes
100%	
Project is an independent bikeway/walkway project covered by the bikeway/walkway Negative Declaration statement; letter of support received	
100%	
Section 4f resources present within the project area, but no known adverse effects	
80%	
Adverse effects (land conversion) to Section 4f/6f resources	

likely

Unknown impacts to Section 4f/6f resources in the project area 6)Right-of-Way (15 Percent of Points) Yes Right-of-way or easements not required 100% Right-of-way or easements has/have been acquired Right-of-way or easements required, offers made 75% Right-of-way or easements required, appraisals made 50% Right-of-way or easements required, parcels identified Right-of-way or easements required, parcels not identified Right-of-way or easements identification has not been completed 0% Anticipated date or date of acquisition 7)Railroad Involvement (25 Percent of Points) No railroad involvement on project Yes Railroad Right-of-Way Agreement is executed (include signature page) 100% Railroad Right-of-Way Agreement required; Agreement has been initiated 60% Railroad Right-of-Way Agreement required; negotiations have begun Railroad Right-of-Way Agreement required; negotiations not begun Anticipated date or date of executed Agreement 8)Construction Documents/Plan (10 Percent of Points) Construction plans completed/approved (include signed title sheet) 100% Construction plans submitted to State Aid for review

75%

Construction plans in progress; at least 30% completion

50%

Construction plans have not been started

Yes

0%

Anticipated date or date of completion

9)Letting

Anticipated Letting Date

													State,		
B /	C		Control Section	T.H. / Roadway							Beginning Ref. Pt.	Ending Ref. Pt.	County, City or Township	Study Period Begins	Study Period Ends
works	heet	t	Section	Roauway			Location				Kti. I t.	Kei. I t.	Township	Degins	Elius
			1910	55	from TH	61 to Ger	neral Sebi	an Drive		2	18+00.423	220+00.306	Hastings	1/1/2011	12/31/2013
			Descripti Proposed		ATMS - 4	5 sionals	unoraded	5 signals inte	erconnected &	z cam	eras				
Accid	ent Dia		1	I WOIR	ATMS .	3 signais	3	3 signais inte	5	4, 7	Cras	6, 90, 98, 99	98, 99		
	Ì	Joues											D 1	0.0	T 1
				2	7			7	→	Pedestrian	Other	Total			
	Fatal	F													
	, (PI)	A		1											1
Study Period:	d Injury	В						2	1						
Number of Crashes	Personal Injury (PI)	С		6				3	8			2		2	21
Crusiics	Property Damage														
	Fatal Da	PD		16		4		2	8		3			5	38
% Change in Crashes	Fa	F		004											
	PI	A		-8%											
*Use FHWA cmfclearingho	FI	В						-8%	-8%						
use for Crash Reduction	ge ty	С		-8%				-8%	-8%			-8%		-8%	
<u>Factors</u>	Property Damage	PD		-8%		-8%		-8%	-8%		-8%			-8%	
	Fatal	F													
		A		-0.08											-0.08
Change in Crashes	PI	В						-0.16	-0.08						-0.24
= No. of		C		-0.48				-0.24	-0.64			-0.16		-0.16	-1.68
crashes X % change in crashes	Property Damage	PD		-1.28		-0.32		-0.16	-0.64		-0.24			-0.40	-3.04
Year (Safety l			Constructi			2019				l					
						2025	TD C	Study Period:	Annual					B/C=	2.09
Project Cost	(exclu	de Rig	ght of Way)	\$ 3	360,000	Type of Crash	Change in Crashes	Change in Crashes	Cos	st per Crash	Annual Benefit		2,0-	
Right of Way Costs (optional)				F			\$	1,100,000		Using present					
Traffic Grov	vth Fa	ctor			3%	%	A	-0.08	-0.03	\$	550,000	\$ 14,667	B=		753,306
Capital Reco	very						В	-0.24	-0.08	\$	160,000	\$ 12,800	C= See "Calculat		360,000
1. Discoun	t Rate	<u> </u>			4.5	%	C	-1.68	-0.56	\$	81,000	\$ 45,360	amortization.	ions sneet f	,
2. Project	Servic	e Lif	e (n)		10	0	PD	PD -3.04 -1.01 \$ 7,400 \$ 7,499							
							Total					\$ 80,325			
·										ted 9-5-2014					


Updated 9-5-2014

Roadway Area Definition

Results

Project Length: 1.92 miles

Project Area: 4.598 sq mi






Project Area


0 1 2 4 6 8















Roadway Area Definition


Results

Project Length: 1.905 miles

Project Area: 1.331 sq mi





LandscapeRSA1











	•	-	•	•	—	•	•	†	/	>	ţ	4
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	*	ર્ન	7	7	f)		7	∱ ∱		7	^	7
Volume (vph)	300	96	398	32	88	28	328	720	36	16	858	289
Satd. Flow (prot)	1681	1724	1583	1770	1796	0	1770	3514	0	1770	3539	1583
Flt Permitted	0.950	0.974		0.950			0.152			0.158		
Satd. Flow (perm)	1681	1724	1583	1770	1796	0	283	3514	0	294	3539	1583
Satd. Flow (RTOR)			462		14			6				72
Confl. Peds. (#/hr)												
Confl. Bikes (#/hr)												
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Growth Factor	116%	116%	116%	116%	116%	116%	116%	116%	116%	116%	116%	116%
Heavy Vehicles (%)	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%
Bus Blockages (#/hr)	0	0	0	0	0	0	0	0	0	0	0	0
Parking (#/hr)												
Mid-Block Traffic (%)		0%			0%			0%			0%	
Shared Lane Traffic (%)	35%											
Lane Group Flow (vph)	226	233	462	37	134	0	380	877	0	19	995	335
Turn Type	Split		NA	Split			pm+pt			pm+pt		Perm
Protected Phases	4	4		3	3		5	2		1	6	
Permitted Phases							2			6		6
Total Split (s)	27.0	27.0	0.0	13.0	13.0	0.0	18.0	40.0	0.0	10.0	32.0	32.0
Total Lost Time (s)	5.5	5.5	4.0	5.5	5.5	4.0	5.0	6.0	4.0	5.0	6.0	6.0
Act Effct Green (s)	17.0	17.0	0.0	7.5	7.5		45.3	44.3		31.5	30.5	30.5
Actuated g/C Ratio	0.19	0.19	0.00	0.08	0.08		0.50	0.49		0.35	0.34	0.34
v/c Ratio	0.71	0.71	1.00	0.25	0.82		1.06	0.51		0.10	0.83	0.57
Control Delay	46.2	46.1	48.2	43.2	74.0		99.1	18.5		22.7	36.2	24.7
Queue Delay	0.0	0.0	0.0	0.0	0.0		0.0	0.0		0.0	0.0	0.0
Total Delay	46.2	46.1	48.2	43.2	74.0		99.1	18.5		22.7	36.2	24.7
LOS	D	D	D	D	Ε		F	В		С	D	С
Approach Delay		47.2			67.3			42.9			33.2	
Approach LOS		D			Е			D			С	
Queue Length 50th (ft)	127	131	0	20	68		~162	151		7	272	121
Queue Length 95th (ft)	197	203	#185	50	#170		#396	278		24	#427	226
Internal Link Dist (ft)		5750			766			2611			2039	
Turn Bay Length (ft)			150				150			100		25
Base Capacity (vph)	402	412	462	148	163		357	1733		191	1198	584
Starvation Cap Reductn	0	0	0	0	0		0	0		0	0	0
Spillback Cap Reductn	0	0	0	0	0		0	0		0	0	0
Storage Cap Reductn	0	0	0	0	0		0	0		0	0	0
Reduced v/c Ratio	0.56	0.57	1.00	0.25	0.82		1.06	0.51		0.10	0.83	0.57

Intersection Summary

Cycle Length: 90

Actuated Cycle Length: 90

Offset: 0 (0%), Referenced to phase 2:NBTL and 6:SBTL, Start of 1st Green

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 1.06


Intersection Signal Delay: 41.5
Intersection Capacity Utilization 86.8%

Intersection LOS: D
ICU Level of Service E

Analysis Period (min) 15

108: TH 55(195) & TH 61(214_216)

- Volume exceeds capacity, queue is theoretically infinite. Queue shown is maximum after two cycles.
- 95th percentile volume exceeds capacity, queue may be longer.
 - Queue shown is maximum after two cycles.



	•	-	\rightarrow	•	←	•	•	†	/	\	ļ	4
Lane Group	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	ሻ	ની	7	7	f)		ሻ	∱ Љ		7	^	7
Volume (vph)	300	96	398	32	88	28	328	720	36	16	858	289
Satd. Flow (prot)	1681	1724	1583	1770	1796	0	1770	3514	0	1770	3539	1583
Flt Permitted	0.950	0.974		0.950			0.189			0.198		
Satd. Flow (perm)	1681	1724	1583	1770	1796	0	352	3514	0	369	3539	1583
Satd. Flow (RTOR)			462		16			8				84
Confl. Peds. (#/hr)												
Confl. Bikes (#/hr)												
Peak Hour Factor	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00
Growth Factor	116%	116%	116%	116%	116%	116%	116%	116%	116%	116%	116%	116%
Heavy Vehicles (%)	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%	2%
Bus Blockages (#/hr)	0	0	0	0	0	0	0	0	0	0	0	0
Parking (#/hr)												
Mid-Block Traffic (%)		0%			0%			0%			0%	
Shared Lane Traffic (%)	35%											
Lane Group Flow (vph)	226	233	462	37	134	0	380	877	0	19	995	335
Turn Type	Split		Perm	Split			pm+pt			pm+pt		Perm
Protected Phases	4	4		3	3		5	2		1	6	
Permitted Phases			4				2			6		6
Total Split (s)	18.0	18.0	18.0	13.0	13.0	0.0	18.0	39.0	0.0	10.0	31.0	31.0
Total Lost Time (s)	5.5	5.5	5.5	5.5	5.5	4.0	5.0	6.0	4.0	5.0	6.0	6.0
Act Effct Green (s)	12.4	12.4	12.4	7.4	7.4		40.2	39.2		26.2	25.2	25.2
Actuated g/C Ratio	0.16	0.16	0.16	0.09	0.09		0.50	0.49		0.33	0.32	0.32
v/c Ratio	0.87	0.88	0.73	0.23	0.74		0.93	0.51		0.09	0.89	0.60
Control Delay	65.9	66.3	11.0	37.3	56.9		60.4	16.0		19.5	38.0	22.5
Queue Delay	0.0	0.0	0.0	0.0	0.0		0.0	0.0		0.0	0.0	0.0
Total Delay	65.9	66.3	11.0	37.3	56.9		60.4	16.0		19.5	38.0	22.5
LOS	Е	Е	В	D	Е		Е	В		В	D	С
Approach Delay		38.5			52.6			29.4			33.9	
Approach LOS		D			D			С			С	
Queue Length 50th (ft)	117	121	0	17	58		109	131		6	248	104
Queue Length 95th (ft)	#246	#251	87	46	#146		#318	233		21	#364	191
Internal Link Dist (ft)		5750			766			2611			2039	
Turn Bay Length (ft)			150				150			100		25
Base Capacity (vph)	263	269	637	166	183		407	1727		209	1117	557
Starvation Cap Reductn	0	0	0	0	0		0	0		0	0	0
Spillback Cap Reductn	0	0	0	0	0		0	0		0	0	0
Storage Cap Reductn	0	0	0	0	0		0	0		0	0	0
Reduced v/c Ratio	0.86	0.87	0.73	0.22	0.73		0.93	0.51		0.09	0.89	0.60

Intersection Summary

Cycle Length: 80

Actuated Cycle Length: 80

Offset: 0 (0%), Referenced to phase 2:NBTL and 6:SBTL, Start of 1st Green

Control Type: Actuated-Coordinated

Maximum v/c Ratio: 0.93

Intersection Signal Delay: 34.4

Intersection Capacity Utilization 86.8%

Intersection LOS: C
ICU Level of Service E

Analysis Period (min) 15

108: TH 55(195) & TH 61(214_216)

95th percentile volume exceeds capacity, queue may be longer.
Queue shown is maximum after two cycles.

Splits and Phases: 108: TH 55(195) & TH 61(214_216)

